# **Dark Elm TileDeck**



## Tile Sizes

1200x196x20mm

## **Coping Profiles**

Square Edge

1200x196x20mm

Bullnose

1200x196x20mm



1200x196x60/20mm



1200x196x100/20mm

\*Non stock item.

Check production lead time, we make to order.





## Dark Elm TileDeck

#### Description

Love the Aussie beach house timber pool deck look? Say G'Day to Dark Elm Tile-Deck, a mid silver grey, timber-look, non-slip, low maintenance porcelain tile! Perfect to achieve an innovative and modern aesthetic around your pool or raised decking platform. It is hard to believe this wood look porcelain tile is not timber! Give the hard yakka the flick, spend the time chilling around your pool instead.

#### Why choose Dark Elm TileDeck?

Dark Elm TileDeck porcelain tiles are hard, dense and durable, making them very resistant to staining. The 'Grip' finish is rated P5 due to the non-slip finish on the tiles, making them ideal for use around swimming pools and outdoor areas. The tiles are accurately sized, cut well and are easy to lay. This product could be the ultimate answer for those who want a timber decking around the pool but are not keen on the future maintenance implications.

#### **Finish**

Grip

#### Maintenance

Minimal maintenance is required. Timber-look, non-slip porcelain tiles! NO ongoing sealing or staining required. Porcelain's dense surface absorbs very little moisture, so spills that might seep into another material and cause a stain, can easily be wiped up with a damp cloth or hosed off. Dark Elm TileDeck generally only needs to be swept and cleaned with water and a mild detergent regularly.

Porcelain tiles do not need sealing due to having little to no porosity. However, some people choose to seal their porcelain, as there is no doubt it makes cleaning easier. Sealing will especially assist with the cleaning of the grout. After sealing their porcelain, some customers have told us that they even vacuum their tiles!! Please ensure you use an appropriate 'porcelain specific' penetrating sealer. We recommend seeking assistance from John from Stone Clean and Seal for advice.

#### Slip Rating (Wet Pendulum)

This tile has a P5 slip rating in the (V) pendulum classification which is the highest wet pendulum rating available under the current standards. (For pool surrounds, a minimum of P4 is required.)



Brisbane HQ/Showroom: 7 Westringia Road, Brisbane Airport QLD 4008 P: (07) 3854 0462 I E: info@pooltile.com.au

Melbourne Showroom: 79 Bazalgette Crescent, Dandenong South VIC 3175
P: 03 9798 2631 | E: melbourne@pooltile.com.au