

# Sand Drift Porcelain




## Tile Sizes



400x400x20mm



600x400x20mm



600x600x20mm

## Coping Profiles

Square Edge

400x400x20mm\*  
600x400x20mm\*  
600x600x20mm\*  
600x400x20mm\*#

Bullnose

400x400x20mm\*  
600x400x20mm\*  
600x600x20mm\*  
600x400x20mm\*#

Dropface  
Single

400x400x60/20mm\*  
600x400x60/20mm)\*  
600x600x60/20mm\*  
600x400x60/20mm\*#

Dropface  
Single

400x400x100/20mm\*  
600x400x100/20mm\*  
600x600x100/20mm\*  
600x400x100/20mm\*#

Dropface  
Triple Joint

400x400x40/20mm\*  
600x400x40/20mm\*

*\*Non stock item.*

*Check production lead time, we make to order.*

*#Coping cut down to 600x400mm from 600x600mm tile*

For more information, go to [www.pooltile.com.au](http://www.pooltile.com.au)



**The  
Pool Tile  
Company...**



SCAN ME

09-2024

# Sand Drift Porcelain

## Description

Meet Sandy, she's stunning! Cool, elegant and yet low maintenance! We know, you think that's not possible but trust us! It's true! She looks her most stunning with her white and blue-grey undertones when accessorised with a sparkling blue water. An ice-cold stunner!

## Why choose Sand Drift?

Sand Drift porcelain tiles are hard, dense and durable, making them very resistant to staining. What's more, the colour variation in the tiles hides marks in between cleans. The Grip finish is rated P5 due to the non-slip finish on the tiles, making them ideal for use around swimming pools and outdoor areas. The surface finish is comfortable on the skin and gentle enough for swimming costumes. The tiles are accurately sized, cut well and are easy to lay. Sand Drift is ideal for projects requiring a classic, upmarket appearance utilising cool tones.

## Finish

Grip

## Maintenance

Minimal maintenance is required. These tiles do not require sealing. Porcelain's dense surface absorbs very little moisture, so spills that might seep into another material and cause a stain, can easily be wiped up with a damp cloth or hosed off. Sand Drift generally only needs to be swept and cleaned with water and a mild detergent regularly. It is the perfect material for those who want a quality natural stone look with very little effort.

Porcelain tiles do not need sealing due to having little to no porosity. However, some people choose to seal their porcelain, as there is no doubt it makes cleaning easier. Sealing will especially assist with the cleaning of the grout. After sealing their porcelain, some customers have told us that they even vacuum their tiles!! Please ensure you use an appropriate 'porcelain specific' penetrating sealer. We recommend seeking assistance from John from Stone Clean and Seal for advice.

## Slip Rating (Wet Pendulum)

This tile has a P5 slip rating in the (V) pendulum classification which is the highest wet pendulum rating available under the current standards. (For pool surrounds, a minimum of P4 is required.)



**The  
Pool Tile  
Company**

[pooltile.com.au](http://pooltile.com.au)

**Brisbane Showroom**  
7 Westringia Road,  
Brisbane Airport QLD 4008  
P: (07) 3854 0462  
E: [info@pooltile.com.au](mailto:info@pooltile.com.au)

**Sydney Showroom**  
5/145 Arthur St, ,  
Homebush West, NSW, 2140  
P: (02) 9145 6966  
E: [sydneyshowroom@pooltile.com.au](mailto:sydneyshowroom@pooltile.com.au)

**Melbourne Showroom**  
79 Bazalgette Crescent,  
Dandenong South VIC 3175  
P: (03) 9798 2631  
E: [melbourneshowroom@pooltile.com.au](mailto:melbourneshowroom@pooltile.com.au)