

Silver Travertine




Tile Sizes



406x406x12mm
406x406x30mm




610x406x12mm
610x406x30mm



Ashlar 12mm (0.743m²/kit)**

Ashlar 30mm (0.743m²/kit)**




Crazy Paving
200-600x30mm




Loose Cobbles
100x100x30mm
203x100x30mm

Coping Profiles




Natural Edge

406x406x30mm
610x406x30mm




Square Edge

406x406x30mm*
610x406x30mm*



Dropface Single

406x406x60/30mm*
610x406x60/30mm*



Rebated Coping

610x406x60/30mm



**The
Pool Tile
Company**

We recommend sealing of all natural stone products.

**Non stock item. Lead time from order approx 8-10 wks*

***This product is sold by kit. You must buy in multiples of kit.*


SCAN for more information or go to www.pooltile.com.au



SCAN ME

07-2025

Silver Travertine



Description

Silver Travertine is a diva in the tile world. She is a cool, stunning headline star with many shades of whites, browns and silvers. She will only go home with those who unconditionally accept and cherish her uniqueness.

Why choose Silver Travertine

Silver Travertine contains a stunning mix of light and medium silver and brown coloured tiles. Often called Platinum Travertine, this material is widely used outdoors and occasionally indoors. Unfilled Travertine has natural holes in the surface adding texture to the finish and a rustic appearance. Some clients instruct the tile layer to in-fill some of the larger holes at the time of grouting. Silver Travertine is hard wearing and its natural colour variation hides marks very effectively. It is very cool underfoot so ideal to use in any climate. It offers high slip resistance. Travertine is accurately sized, cuts well and is easy to lay.

Finish

Natural Edge and Unfilled

Maintenance

Requires sealing. Seal with penetrating sealer to make cleaning easier. Use pH neutral cleaners. Do not use acid to clean.

Slip Rating (Wet Pendulum)

This tile has a P4 - P5 slip rating in the (V) pendulum classification which is the highest wet pendulum rating available under the current standards. (For pool surrounds, a minimum of P4 is required.)



The
**Pool Tile
Company**

pooltile.com.au

Brisbane Showroom

7 Westringia Road,
Brisbane Airport QLD 4008
P: (07) 3854 0462
E: info@pooltile.com.au

Sydney Showroom

5/145 Arthur St,
Homebush West, NSW, 2140
P: (02) 9145 6966
E: sydneyshowroom@pooltile.com.au

Melbourne Showroom

79 Bazalgette Crescent,
Dandenong South VIC 3175
P: (03) 9798 2631
E: melbourneshowroom@pooltile.com.au